



MODELO / MODEL	PLUS MONOLITH (Pearl, Beige)		
FOTO / PICTURE			
FORMATO / SIZE	60X60 cms. (20mm.) RECT.		
GRUPO / GROUP	Bla		
TIPO / TYPE	PORCELANICO ESMALTADO / Glazed Porcelain Tile		
<u>DESCRIPCION DEL TEST / TEST DESCRIPTION</u>	<u>VALOR DEL TEST / TEST VALUE</u>		<u>NORMA / STANDARD</u>
ABSORCIÓN DE AGUA / WATER ABSORPTION	AA < 0,5%	Cumple / Passed	UNE-EN-ISO 10545-3
FUERZA DE ROTURA / BREAKING STRENGTH	> 1300 N	Cumple / Passed	UNE-EN-ISO 10545-4
RESISTENCIA A LA FLEXIÓN / RESISTANCE OF FLEXION	> 35 N/mm2	Cumple / Passed	UNE-EN-ISO 10545-4
RESISTENCIA AL IMPACTO /		Cumple / Passed	UNE-EN-ISO 10545-5
ABRASION SUPERFICIAL / SURFACE ABRASION	Clase / Class	PEI IV	UNE-EN-ISO 10545-7
RESISTENCIA AL CUARTEO / CRACKING RESISTANCE	Requerido / Requested	Cumple / Passed	UNE-EN-ISO 10545-11
RESISTENCIA A LA HELADA / FROST RESISTANCE	Requerido / Requested	Cumple / Passed	UNE-EN-ISO 10545-12
RESISTENCIA QUIMICA / CHEMICAL RESISTANCE	(PRODUCTOS DOMESTICOS Y DE PISCINA / Domestic & Swimming Pool Products) Mínimo / Minimum GB	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LOS ACIDOS / ACID RESISTANCE	GHA	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LAS BASES / ALKALINE RESISTANCE	GHA	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LAS MANCHAS / RESISTANCE TO STAINS	Mínimo / Minimum Class 3	Cumple / Passed	UNE-EN-ISO 10545-14
RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE	Metodo Disponible / Available Method	R11	DIN 51130:2014-5
RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE	Metodo Disponible / Available Method	Class 3	UNE-ENV 12633:2003
SLIP RESISTANCE	D.C.O.F.	0,71	ANSI A137. 1:2012. 9.6
RESISTENCIA AL RAYADO / HARDNESS (MOHS)	Mínimo / Minimum 3	Cumple / Passed	EN 101